



**COOKING**

*ECO COOK*

*POWER COOK*





 COOKING

# ECO COOK

|                        |       |
|------------------------|-------|
| <b>Eco Cook Series</b> | 24-25 |
| Ranges                 | 26-28 |
| Stoves                 | 29    |
| Tilting bratt pan      | 29    |
| Fry-tops               | 30    |
| Neutral tables         | 30    |

**ASBER ECO COOK** series is a 700-mm depth European modular cooking range, built to meet the most demanding chef needs whilst reducing all non-value added elements.

The result is a cooking range with high-power, first-class burners and plates, entirely made of stainless steel, with a fully welded structure

to achieve a sturdily built, durable solution. A simple, robust and cost-effective answer for any cooking operations.

All appliances have also been designed with a recognizable aesthetics. To ensure maximum hygiene, worktop surfaces are smooth and removable. All models are in accordance with the international standards of safety and hygiene, bearing Certigaz and CE approval.

**GAS RANGES**



Heavy-duty reinforced control knobs on the front panel.



Smooth surface for easy cleaning. Grids made of enameled iron, heavy and stable for safe cooking.



Open burners with 1-crown burner of 4.5 kW or 2-crown burners of 8 kW with possible combinations depending of number of burners of each model. Robust crowns with high-efficiency burners and provided with a flame safety device. Pilot ignition covered to avoid the breakage.

A complete range of products including 2, 4 and 6 burners with and without legs.



## ELECTRIC RANGES



Complete range of electric ranges with 400, 800 and 1200 mm width models with 2, 4 or 6 plates. Stainless steel construction, provided. High-efficiency electric plates made of cast iron with built-in shielded resistors and safety overheat protection. 2,6 kW of power for each plate. Smooth surface easy to clean.

Power controlled by 6-position switch. Light indicator shows when the plate is active.



## GAS STOVE



High-efficiency 2-crown burner of 9 kW.

Made of stainless steel, sturdy and resistant to corrosion. Light and portable. Heavy-duty reinforced control knobs on the front panel.




## ELECTRIC TILTING BRATT PAN



Made of stainless steel. Manual turnover of the pan.

Smooth temperature regulation between 50°C and 300°C, thermostat control for safety usage.



## GAS AND ELECTRIC FRY-TOP



A complete range of gas or electric fry-tops, 400 and 800 mm wide.

Cooking surface designed to roast directly on the plate surface. The plate made of special steel with high heat transfer.

Removable steel pan for fat collection.





GRE-400-11T

 **GAS RANGES WITH 2 BURNERS**

- Made of stainless steel.
- High-power gas burners: 1-crown burner of 4,5 kW and/or 2-crown burner of 8 kw.
- Burners with flame safety device.
- Robust, enamelled grills, safety valves and thermocouple.
- Gas connection: ½".
- Height-adjustable legs.
- Assembled with injectors for use with natural gas (NG) or (LPG).

| Model          | Reference       | Dimensions (mm) | Power kW (Kcal/h) | Gas type | N° of burners 4,5 kW | N° of burners 8 kW |
|----------------|-----------------|-----------------|-------------------|----------|----------------------|--------------------|
| GRE-400-20T    | <b>19023366</b> | 400 x 700 x 310 | 9 (7,74)          | LPG      | 2                    | -                  |
| GRE-400-20T NG | <b>19023367</b> | 400 x 700 x 310 | 9 (7,74)          | NG       | 2                    | -                  |
| GRE-400-11T    | <b>19023362</b> | 400 x 700 x 310 | 12,5 (10,75)      | LPG      | 1                    | 1                  |
| GRE-400-11T NG | <b>19023363</b> | 400 x 700 x 310 | 12,5 (10,75)      | NG       | 1                    | 1                  |
| GRE-400-02T    | <b>19023358</b> | 400 x 700 x 310 | 16 (13,76)        | LPG      | -                    | 2                  |
| GRE-400-02T NG | <b>19023359</b> | 400 x 700 x 310 | 16 (13,76)        | NG       | -                    | 2                  |



GRE-800-22T

 **GAS RANGES WITH 4 BURNERS**

- Made of stainless steel.
- High-power gas burners: 1-crown burner of 4,5 kW and/or 2-crown burner of 8 kw.
- Burners with flame safety device.
- Robust, enamelled grills, safety valves and thermocouple.
- Gas connection: ½".
- Height-adjustable legs.
- Assembled with injectors for use with natural gas (NG) or (LPG).

| Model          | Reference       | Dimensions (mm) | Power kW (Kcal/h) | Gas type | N° of burners 4,5 kW | N° of burners 8 kW |
|----------------|-----------------|-----------------|-------------------|----------|----------------------|--------------------|
| GRE-800-31T    | <b>19023378</b> | 800 x 700 x 310 | 21,5 (18,49)      | LPG      | 3                    | 1                  |
| GRE-800-31T NG | <b>19023379</b> | 800 x 700 x 310 | 21,5 (18,49)      | NG       | 3                    | 1                  |
| GRE-800-22T    | <b>19023374</b> | 800 x 700 x 310 | 25 (21,5)         | LPG      | 2                    | 2                  |
| GRE-800-22T NG | <b>19023375</b> | 800 x 700 x 310 | 25 (21,5)         | NG       | 2                    | 2                  |
| GRE-800-13T    | <b>19023370</b> | 800 x 700 x 310 | 28,5 (24,51)      | LPG      | 1                    | 3                  |
| GRE-800-13T NG | <b>19022227</b> | 800 x 700 x 310 | 28,5 (24,51)      | NG       | 1                    | 3                  |



GRE-1200-33T

 **GAS RANGES WITH 6 BURNERS**

- Made of stainless steel.
- High-power gas burners: 1-crown burner of 4,5 kW and/or 2-crown burner of 8 kw.
- Burners with flame safety device.
- Robust, enamelled grills, safety valves and thermocouple.
- Gas connection: ½".
- Height-adjustable legs.
- Assembled with injectors for use with natural gas (NG) or (LPG).

| Model           | Reference       | Dimensions (mm)  | Power kW (Kcal/h) | Gas type | N° of burners 4,5 kW | N° of burners 8 kW |
|-----------------|-----------------|------------------|-------------------|----------|----------------------|--------------------|
| GRE-1200-42T    | <b>19023354</b> | 1200 x 700 x 310 | 34 (29,24)        | LPG      | 4                    | 2                  |
| GRE-1200-42T NG | <b>19023355</b> | 1200 x 700 x 310 | 34 (29,24)        | NG       | 4                    | 2                  |
| GRE-1200-33T    | <b>19023350</b> | 1200 x 700 x 310 | 37,5 (32,25)      | LPG      | 3                    | 3                  |
| GRE-1200-33T NG | <b>19023351</b> | 1200 x 700 x 310 | 37,5 (32,25)      | NG       | 3                    | 3                  |
| GRE-1200-24T    | <b>19023346</b> | 1200 x 700 x 310 | 41 (35,26)        | LPG      | 2                    | 4                  |
| GRE-1200-24T NG | <b>19023347</b> | 1200 x 700 x 310 | 41 (35,26)        | NG       | 2                    | 4                  |



GRE-400-11

### GAS RANGES WITH 2 BURNERS

- Made of stainless steel.
- High-power gas burners: 1-crown burner of 4,5 kW and/or 2-crown burner of 8 kw.
- Burners with flame safety device.
- Robust, enamelled grills, safety valves and thermocouple.
- Gas connection: ½".
- Height-adjustable legs.
- Assembled with injectors for use with natural gas (NG) or (LPG).

| Model         | Reference | Dimensions (mm) | Power kW (Kcal/h) | Gas type | N° of burners 4,5 kW | N° of burners 8 kW |
|---------------|-----------|-----------------|-------------------|----------|----------------------|--------------------|
| GRE-400-20    | 19023364  | 400 x 700 x 850 | 9 (7,74)          | LPG      | 2                    | -                  |
| GRE-400-20 NG | 19023365  | 400 x 700 x 850 | 9 (7,74)          | NG       | 2                    | -                  |
| GRE-400-11    | 19023360  | 400 x 700 x 850 | 12,5 (10,75)      | LPG      | 1                    | 1                  |
| GRE-400-11 NG | 19023361  | 400 x 700 x 850 | 12,5 (10,75)      | NG       | 1                    | 1                  |
| GRE-400-02    | 19023356  | 400 x 700 x 850 | 16 (13,76)        | LPG      | -                    | 2                  |
| GRE-400-02 NG | 19023357  | 400 x 700 x 850 | 16 (13,76)        | NG       | -                    | 2                  |



GRE-800-22

### GAS RANGES WITH 4 BURNERS

- Made of stainless steel.
- High-power gas burners: 1-crown burner of 4,5 kW and/or 2-crown burner of 8 kw.
- Burners with flame safety device.
- Robust, enamelled grills, safety valves and thermocouple.
- Gas connection: ½".
- Height-adjustable legs.
- Assembled with injectors for use with natural gas (NG) or (LPG).

| Model         | Reference | Dimensions (mm) | Power kW (Kcal/h) | Gas type | N° of burners 4,5 kW | N° of burners 8 kW |
|---------------|-----------|-----------------|-------------------|----------|----------------------|--------------------|
| GRE-800-31    | 19023376  | 800 x 700 x 850 | 21,5 (18,49)      | LPG      | 3                    | 1                  |
| GRE-800-31 NG | 19023377  | 800 x 700 x 850 | 21,5 (18,49)      | NG       | 3                    | 1                  |
| GRE-800-22    | 19023372  | 800 x 700 x 850 | 25 (21,5)         | LPG      | 2                    | 2                  |
| GRE-800-22 NG | 19023373  | 800 x 700 x 850 | 25 (21,5)         | NG       | 2                    | 2                  |
| GRE-800-13    | 19023368  | 800 x 700 x 850 | 28,5 (24,51)      | LPG      | 1                    | 3                  |
| GRE-800-13 NG | 19022228  | 800 x 700 x 850 | 28,5 (24,51)      | NG       | 1                    | 3                  |



GRE-1200-33

### GAS RANGES WITH 6 BURNERS

- Made of stainless steel.
- High-power gas burners: 1-crown burner of 4,5 kW and/or 2-crown burner of 8 kw.
- Burners with flame safety device.
- Robust, enamelled grills, safety valves and thermocouple.
- Gas connection: ½".
- Height-adjustable legs.
- Assembled with injectors for use with natural gas (NG) or (LPG).

| Model          | Reference | Dimensions (mm)  | Power kW (Kcal/h) | Gas type | N° of burners 4,5 kW | N° of burners 8 kW |
|----------------|-----------|------------------|-------------------|----------|----------------------|--------------------|
| GRE-1200-42    | 19023352  | 1200 x 700 x 850 | 34 (29,24)        | LPG      | 4                    | 2                  |
| GRE-1200-42 NG | 19023353  | 1200 x 700 x 850 | 34 (29,24)        | NG       | 4                    | 2                  |
| GRE-1200-33    | 19023348  | 1200 x 700 x 850 | 37,5 (32,25)      | LPG      | 3                    | 3                  |
| GRE-1200-33 NG | 19023349  | 1200 x 700 x 850 | 37,5 (32,25)      | NG       | 3                    | 3                  |
| GRE-1200-24    | 19023344  | 1200 x 700 x 850 | 41 (35,26)        | LPG      | 2                    | 4                  |
| GRE-1200-24 NG | 19023345  | 1200 x 700 x 850 | 41 (35,26)        | NG       | 2                    | 4                  |



ERE-400T



ERE-800T

 **TABLE-TOP ELECTRIC RANGES**

- Models available in 3 different widths: 400, 800 and 1200 mm.
- Made of stainless steel.
- 223 mm diameter plates.
- Stamped stainless steel worktop to prevent liquid spillages.
- Temperature regulation by a 6-position switch with corresponding operating pilot. Safety overheat protection.
- 2,6 kW power in each plate.
- Height-adjustable legs.

| Model     | Reference       | Dimensions (mm)  | Power kW (Kcal/h) | Voltage (V)           | N° of burners<br>2,6 kW |
|-----------|-----------------|------------------|-------------------|-----------------------|-------------------------|
| ERE-400T  | <b>19023332</b> | 400 x 700 x 285  | 5,2 (4,472)       | 380-415/3N - 50/60 Hz | 2                       |
| ERE-800T  | <b>19023334</b> | 800 x 700 x 285  | 10,4 (8,944)      | 380-415/3N - 50/60 Hz | 4                       |
| ERE-1200T | <b>19023330</b> | 1200 x 700 x 285 | 15,6 (13,416)     | 380-415/3N - 50/60 Hz | 6                       |



ERE-400



ERE-800

 **STANDING ELECTRIC RANGES**

- Models available in 3 different widths: 400, 800 and 1200 mm.
- Made of stainless steel.
- 223 mm diameter plates.
- Stamped stainless steel worktop to prevent liquid spillages.
- Temperature regulation by a 6-position switch with corresponding operating pilot. Safety overheat protection.
- 2,6 kW power in each plate.
- Height-adjustable legs.

| Model    | Reference       | Dimensions (mm)  | Power kW (Kcal/h) | Voltage (V)           | N° of burners<br>2,6 kW |
|----------|-----------------|------------------|-------------------|-----------------------|-------------------------|
| ERE-400  | <b>19023331</b> | 400 x 700 x 850  | 5,2 (4,472)       | 380-415/3N - 50/60 Hz | 2                       |
| ERE-800  | <b>19023333</b> | 800 x 700 x 850  | 10,4 (8,944)      | 380-415/3N - 50/60 Hz | 4                       |
| ERE-1200 | <b>19023329</b> | 1200 x 700 x 850 | 15,6 (13,416)     | 380-415/3N - 50/60 Hz | 6                       |





GSPE-600

**GAS STOVE WITH 1 BURNER**

- Made of stainless steel.
- 9 kW high-efficiency 2-crown burner.
- Pilot burner.
- Gas connection: 1/2".
- Available two different height.
- Height-adjustable legs.
- Assembled with injectors for use with natural gas (NG) or (LPG).

| Model        | Reference | Dimensions (mm) | Power kW (Kcal/h) | Gas type |
|--------------|-----------|-----------------|-------------------|----------|
| GSPE-600     | 19023382  | 580 x 580 x 440 | 9 (7,74)          | LPG      |
| GSPE-600 NG  | 19023383  | 580 x 580 x 440 | 9 (7,74)          | NG       |
| GSPE-600H    | 19023384  | 580 x 580 x 720 | 9 (7,74)          | LPG      |
| GSPE-600H NG | 19023385  | 580 x 580 x 720 | 9 (7,74)          | NG       |



GSPE-1200

**GAS STOVE WITH 2 BURNERS**

- Made of stainless steel.
- 2 x 9 kW high-efficiency 2-crown burner.
- Pilot burner.
- Gas connection: 1/2".
- Height-adjustable legs.
- Assembled with injectors for use with natural gas (NG) or (LPG).

| Model        | Reference | Dimensions (mm)  | Power kW (Kcal/h) | Gas type |
|--------------|-----------|------------------|-------------------|----------|
| GSPE-1200    | 19023380  | 1160 x 580 x 440 | 2 x 9 (15,48)     | LPG      |
| GSPE-1200 NG | 19023381  | 1160 x 580 x 440 | 2 x 9 (15,48)     | NG       |



ETBPE-800

**ELECTRIC TILTING BRATT PAN**

- Made of stainless steel.
- Smooth temperature regulation between 50°C and 300°C, thermostat control for safety usage.
- Manual turnover of the pan.
- Working capacity: 0,25 m<sup>2</sup> (30 liters).
- Tank depth: 120 mm.

| Model     | Reference | Dimensions (mm) | Power kW (Kcal/h) | Voltage (V)           |
|-----------|-----------|-----------------|-------------------|-----------------------|
| ETBPE-800 | 19023335  | 700 x 660 x 850 | 6 (5,16)          | 380-415/3N - 50/60 Hz |



GFTE-400



GFTE-400T

 **GAS FRY-TOP**

- Standing and table-top models available in two different widths: 400 and 800 mm.
- Made of stainless steel.
- Cooking plate made of special steel with high heat transfer, designed to cook directly on its surface.
- Stainless steel burners with ignition pilot.
- Side and rear protection, avoiding spillages.
- Burner flame control using the valve of "maximum-minimum" type.
- 1 or 2 cooking surface depending on width of the model:
  - GFTE-400 (1 cooking surface).
  - GFTE-800 (2 cooking surface).
- Removable steel drip pan for fat collection.
- Gas connection: 1/2".
- Height-adjustable legs.
- Assembled with injectors for use with natural gas (NG) or (LPG).



| Model        | Reference | Dimensions (mm) | Power kW (Kcal/h) | Legs | Gas type |
|--------------|-----------|-----------------|-------------------|------|----------|
| GFTE-400T    | 19023338  | 400 x 700 x 230 | 4,5 (3,87)        | Not  | LPG      |
| GFTE-400T NG | 19023339  | 400 x 700 x 230 | 4,5 (3,87)        | Not  | NG       |
| GFTE-800T    | 19022222  | 800 x 700 x 230 | 9 (7,74)          | Not  | LPG      |
| GFTE-800T NG | 19023343  | 800 x 700 x 230 | 9 (7,74)          | Not  | NG       |
| GFTE-400     | 19023336  | 400 x 700 x 850 | 4,5 (3,87)        | Yes  | LPG      |
| GFTE-400 NG  | 19023337  | 400 x 700 x 850 | 4,5 (3,87)        | Yes  | NG       |
| GFTE-800     | 19023340  | 800 x 700 x 850 | 9 (7,74)          | Yes  | LPG      |
| GFTE-800 NG  | 19023341  | 800 x 700 x 850 | 9 (7,74)          | Yes  | NG       |



EFTE-800



EFTE-800T

 **ELECTRIC FRY-TOP**

- Standing and table-top models available in two different widths: 400 and 800 mm.
- Made of stainless steel.
- Cooking plate made of special steel with high heat transfer, designed to cook directly on its surface.
- Side and rear protection, avoiding spillages.
- 6-position switch, smooth temperature regulation between 50°C and 300°C, thermostat control and light indicator for safety usage.
- 1 or 2 cooking surface depending on width of the model:
  - EFTE-400 (1 cooking surface).
  - EFTE-800 (2 cooking surface).
- Removable steel drip pan for fat collection.
- Height-adjustable legs.

| Model     | Reference | Dimensions (mm) | Power kW (Kcal/h) | Legs | Voltage (V)           |
|-----------|-----------|-----------------|-------------------|------|-----------------------|
| EFTE-400T | 19023326  | 400 x 700 x 230 | 4,2 (3,61)        | Not  | 380-415/3N - 50/60 Hz |
| EFTE-800T | 19023328  | 800 x 700 x 230 | 8,4 (7,22)        | Not  | 380-415/3N - 50/60 Hz |
| EFTE-400  | 19023325  | 400 x 700 x 850 | 4,2 (3,61)        | Yes  | 380-415/3N - 50/60 Hz |
| EFTE-800  | 19023327  | 800 x 700 x 850 | 8,4 (7,22)        | Yes  | 380-415/3N - 50/60 Hz |



WTE-400



WTE-800

**NEUTRAL TABLES**

- Made of stainless steel, designed for table-top models.
- Additional, completely flat and smooth, work surface.
- Table frame ensures excellent stability while working on it.
- Solid and sturdy structure.
- Height-adjustable legs.

| Model   | Reference | Dimensions      |
|---------|-----------|-----------------|
| WTE-400 | 19023386  | 400 x 700 x 850 |
| WTE-800 | 19023387  | 800 x 700 x 850 |



 COOKING

# POWER COOK

|                          |       |
|--------------------------|-------|
| <b>Power Cook Series</b> | 48-49 |
| Ranges                   | 50-51 |
| Ovens                    | 51    |

**ASBER POWER COOK** series is a heavy-duty cooking range designed to meet the most demanding needs of Eastern European professional kitchens. Truly robust and durable, these appliances are intelligently designed to be the perfect answer for high-production cooking applications.

Entirely made of stainless steel, each model offers unmatched performance, combining proven control with quality, and also bearing the GOST certificate of conformity.

## ELECTRIC RANGES

- 295 x 418 mm heavy-duty cast-iron hot plates.
- Side countertops can be dismantled to be used as part of a cooking line-up.
- Control panel with switches and controls lights for safety usage.
- Temperature regulation made with large 4-position switch knobs that define the heating degree: low, average and high.
- Oven's temperature controlled by 4-positions switch knob (selection of heating section), thermo regulator (automatic maintenance of set temperature) and control lights.



Side countertops easily removable to be used in a cooking line-up.



Big and robust control knobs on the front panel.



Hot plates flat surface enables cookware easy shifting and multiple cooking positions.



Heavy-duty cast-iron hot plates.

# GAS RANGES

## Main features

- High-efficiency 2-crown burners with flame safety device: 3 x 4 kW and 1 x 8 kW. Heavy-duty grids made of enameled iron, very stable for sale cooking.
- Control panel with gas valves. Smooth flame regulation by 3-positions heavy-duty reinforced knobs.
- Temperature controlled by 4-positions switch (selection of heating section), thermo regulator (automatic maintenance of set temperature) and indication light.



Heavy-duty grids made of enameled iron.



High-efficiency 2-crown burners.



## Main features

- Every oven section consists of a metal chamber with an easy-opening drop-down door and two tubular heaters located on the top and bottom of the chamber.
- Removable rails with guides, fixed on lateral walls, are intended for tray installation at the level need.



Gastronorm compatible 2/1 GN oven chamber with single drop-down door.



Heat resistant oven door handle.



ASE-40



ASE-60

 **ELECTRIC RANGES WITH SHELF**

- Made of stainless steel and sturdily built.
- Upper cooking module with cast-iron heating plates and bottom undershelf.
- Long-lasting, heavy-duty cast-iron hot plates ensures quick and uniform heating up to 480°C.
- Heating plate dimensions: 295 x 418 mm.
- Plates power: 4 x 3 kW in ASE-40 and 6 x 3 kW in ASE-60.
- Plane surface of the hot plates ensures easy shifting of the cookware and multiple cooking positions.
- Regulation of temperature through a thermostat.
- Can be used independently (with side countertops) or as an appliance in a cooking line-up removing side countertops with great ease.
- Removable tray to collect liquid spillages, enabling quickly and easy cleaning operations.
- Easy cleaning thanks to its intelligent design.
- Height-adjustable legs.

| Model  | Reference       | Dimensions (mm)<br>(with side countertops) | Power<br>kW (Kcal/h) | Voltage<br>(V)       | N° of plates |
|--------|-----------------|--|----------------------|----------------------|--------------|
| ASE-40 | <b>19022499</b> | 840 x 850 x 860 (1050 x 850 x 860)         | 12 (10,32)           | 230-415/3N - 50/60Hz | 4            |
| ASE-60 | <b>19022500</b> | 1262 x 850 x 860 (1470 x 850 x 860)        | 18 (15,48)           | 230-415/3N - 50/60Hz | 6            |



ASE-41  
Cooker with oven.



ASE-61  
Cooker with oven and neutral cabinet.

 **ELECTRIC RANGES WITH OVEN**

- Made of stainless steel and sturdily built.
  - Upper cooking module with cast-iron heating plates and bottom undershelf.
  - Long-lasting, heavy-duty cast-iron hot plates ensures quick and uniform heating up to 480°C.
  - Heating plate dimensions: 295 x 418 mm.
  - Plates power: 4 x 3 kW in ASE-41 and 6 x 3 kW in ASE-61.
  - Plane surface of the hot plates ensures easy shifting of the cookware and multiple cooking positions.
  - Regulation of temperature through a thermostat.
  - Can be used independently (with side countertops) or as an appliance in a cooking line-up removing side countertops with great ease.
  - Removable tray to collect liquid spillages, enabling quickly and easy cleaning operations.
  - Easy cleaning thanks to its intelligent design.
  - Height-adjustable legs.
- OVEN FEATURES:**
- Chamber dimensions: 650 x 530 x 295 mm, usable area: 0,384 m2.
  - Gastronorm compatible 2/1 GN electric oven with single drop down door.
  - Working temperature from 50 to 270°C. Heating time to achieve 270°C - 30 minutes.
  - Heat-proof door handle.
  - 6 kW power.

| Model  | Reference       | Dimensions (mm)<br>(with side countertops) | Power<br>kW (Kcal/h) | Voltage<br>(V)       | N° of plates |
|--------|-----------------|--|----------------------|----------------------|--------------|
| ASE-41 | <b>19022507</b> | 840 x 850 x 860 (1050 x 850 x 860)         | 18 (15,48)           | 230-415/3N - 50/60Hz | 4            |
| ASE-61 | <b>19022502</b> | 1262 x 850 x 860 (1470 x 850 x 860)        | 24 (20,64)           | 230-415/3N - 50/60Hz | 6            |



**ASG-40**  
Gas range with shelf.



**ASG-41**  
Gas range with oven.

**GAS RANGES WITH SHELF OR OVEN**

- Made of stainless steel and sturdily built.
- Can be used independently or as an appliance in a cooking line-up.
- High efficiency open top burners with robust enameled grills, security valve and thermocouple.
- 4 gas burners: 3 x 4 kW and 1 x 8 kW.
- Removable tray to collect liquid spillages, enabling quickly and easy cleaning operations.
- Easy cleaning thanks to its intelligent design.
- Height-adjustable legs.
- Supplied and assembled with injectors for use with natural gas (NG) and (LPG).

**OVEN FEATURES:**

- Chamber dimensions: 530 x 650 x 295 mm, usable area: 0,384 m<sup>2</sup>.
- Gastronorm compatible 2/1 GN gas oven with single drop-down door.
- Working temperature from 50 to 270°C. Heating time to achieve 270°C – 30 min.
- Temperature controlled with thermo-regulated 7-position gas valve.
- Piezoelectric unit to light the burner in the oven.
- Heat-proof door handle.
- 8 kW power.

| Model  | Reference       | Dimensions      | Power kW (Kcal/h) | Description | N° of burners |
|--------|-----------------|-----------------|-------------------|-------------|---------------|
| ASG-40 | <b>19022229</b> | 850 x 900 x 860 | 20 (17,2)         | with shelf  | 4             |
| ASG-41 | <b>19022223</b> | 850 x 900 x 860 | 28 (24,08)        | with oven   | 4             |



**ASE-02**  
Electric ovens with shelf.



**ASE-03**  
Electric ovens without shelf.

**ELECTRIC OVENS**

- Made of stainless steel and sturdily built.
- Heavy-duty electric ovens with high-energy performance to bake bread, meat, biscuits, pizza, cakes, etc.
- Chamber dimensions: 530 x 650 x 295 mm, usable area: 0,384 m<sup>2</sup>.
- Gastronorm compatible 2/1 GN electric oven with single drop-down door.
- Working temperature from 50 to 270°C. Heating time to achieve 270°C – 30 min.
- Heat-proof door handle.
- Easy cleaning thanks to its intelligent design to facility the operations.
- Height-adjustable legs.
- Power: 2 x 6 kW in ASE-02 and 3 x 6 kW in ASE-03.

| Model  | Reference       | Dimensions (mm)  | Power kW (Kcal/h) | Voltage (V)          | N° of chambers |
|--------|-----------------|------------------|-------------------|----------------------|----------------|
| ASE-02 | <b>19022501</b> | 840 x 840 x 1480 | 12 (10,32)        | 230-415/3N - 50/60Hz | 2              |
| ASE-03 | <b>19022231</b> | 840 x 840 x 1480 | 18 (15,48)        | 230-415/3N - 50/60Hz | 3              |



**MULTI-SOLUTION  
MANUFACTURER OF  
FOODSERVICE  
EQUIPMENT**



**Asber Professional**  
Taking Your Business Forward

Contact us at **[www.asberprofessional.com](http://www.asberprofessional.com)**

We'd love to learn how we can partner with you.  
This catalog has been printed using eco-friendly materials and procedures.